



HIGH-EFFICIENT HARDMOUNT INDUSTRIAL WASHER-EXTRACTORS

IA332
35KG

IA520
52KG

FEATURES

- Rigid mounted, normal spin, 100G factor
- Stainless steel top and front panel, black side panels
- Stainless steel drum and tub
- Aries - easy to use microprocessor
- Patented soap hopper
- High capacity water inlets
- Large drain valves (2 x Ø 76 mm)
- Easy access to all vital parts from the front
- Large door opening for easy loading & unloading

OPTIONS

- 150G factor execution (IA332)
- Aries Elite - Fully programmable
- Coin operated timer
- Stainless steel side panels
- USB plug (on the back panel)
- Liquid soap connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- 3rd water inlet



ERGONOMICAL
CONSTRUCTION



LARGE DOOR
OPENING



LOW WATER
CONSUMPTION



LOW ENERGY
CONSUMPTION

THE SMART LAUNDRY PARTNER

	IA332	IA520
INNERDRUM		
CAPACITY 10:1 (KG)	35	52
CAPACITY 9:1 (KG)	39	58
VOLUME (L)	332	520
DIAMETER (MM)	914	914
DRUM SPEED		
WASH (RPM)	38	38
EXTRACTION (RPM)	440	440
G-FACTOR	100 (optional 150- 540 rpm)	100
HEATING		
ELECTRICITY (KW)	2,2	4,0
STEAM (BAR)	1 - 8	1 - 8
HOT WATER (°C)	90	90
SOUND PRESSURE LEVEL (DB) (A)	< 65	< 65
WATER VALVES CONNECTION (BSP)	3/4"	1"
WATER PRESSURE (KPA)	100-800	100-800
REC. WATER PRESSURE (KPA)	300-500	300-500
WATER INLET (L/MIN)	66-188	183-518
DRAIN VALVE OUTER (MM)	2 x 76	2 x 76
FLOW AMOUNT WITH DRAIN VALVE (L/MIN)	2 x 210	2 x 210
STEAM VALVE CONNECTION (BSP)	3/4"	3/4"
STEAM PRESSURE (KPA)	100-800	100-800
TRANSPORT DATA		
GROSS WEIGHT (KG)	450	570
NET WEIGHT (KG)	410	520
PACKING DIMENSIONS H x W x D (MM)	1625 x 1088 x 1060	1625 x 1088 x 1345

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	S	T
IA332	1060	1030	1500	936	465	318	120	1326	1366	113	248	383	671	1349	1413	528	66	145	482
IA520	1060	1315	1500	1221	465	318	120	1414	1374	88	223	363	671	1349	1332	528	66	145	482
	width	depth	height																

