



INDUSTRIAL TUMBLE DRYERS WITH HEAT PUMP

IHP190 | IHP250 | IHP285 | IHP345
9,5KG | 12,5KG | 14,3KG | 17,3KG

FEATURES

- Heat pump
- Standard stainless steel drum with large diameter
- Easy to use microprocessor (Easy)
- Combination of radial and axial airflow concept:
 - Maximal heat transfer
 - Low energy consumption
- Large drain valve (Ø 76 mm)
- Large door opening for easy loading & unloading
- Self cleaning lint screen

OPTIONS


- Stainless steel side front
- Reversing drum
- Full control programmer (Flex)
- Residual moisture control
 - Safe drying of delicate linen
 - Humidity detection in %
 - Ideal in combination with wet cleaning
 - Ideal for dry cleaners, fire departments
 - Available on Easy and Flex Control
- Coin operated version



HEAT PUMP



STANDARD
STAINLESS STEEL
DRUM



ENERGY
EFFICIENT

	IHP190	IHP250	IHP285	IHP345
INNERDRUM				
CAPACITY 20:1 (KG)	9,5	12,5	14,3	17,3
CAPACITY 25:1 (KG)	7,6	10	11,4	13,8
VOLUME (L)	190	250	285	345
DIAMETER (MM)	760	760	760	760
DRYING AVERAGE (G/MIN)	122	126	120	120
MOTORS				
FAN (KW)	0,30	0,30	0,30	0,30
DRIVE (KW)	0,18	0,25	0,25	0,25
HEAT PUMP				
ELECTRICAL CONNECTION	3 x 380-415V / 50Hz+N (standard)	3 x 380-415V / 50Hz+N (standard)	3 x 380-415V / 50Hz+N (standard)	3 x 380-415V / 50Hz+N (standard)
ENERGY (KW)	2,9	2,9	2,9	2,9
PROGRAMMER				
EASY CONTROL	standard	standard	standard	standard
FLEX CONTROL	optional	optional	optional	optional
TRANSPORT DATA				
DIMENSIONS H X W X D (MM)	1465 x 795 x 1275	1680 x 795 x 1525	1680 x 795 x 1615	1680 x 795 x 1735
GROSS WEIGHT (KG)	305	385	400	400
NET WEIGHT (KG)	290	350	360	375

Energy consumption comparison CONVENTIONAL DRYER VS. HEAT PUMP DRYER

